



THE INDUSTRY STANDARD FOR STEEL IBCS



SOLUTIONS IN BULK HANDLING

www.snyderibcs.com

**S
U
P
E
R
T
A
I
N
E
R**

SUPERTAINER

IN BULK HANDLING • SOLUTIONS IN BULK HANDLING • SOLUTIONS IN BULK HANDLING • SOLUTIONS IN BULK HANDLING • SOLUTIONS IN BULK HANDLING • SOLUTIONS IN BULK HANDLING • SOLUTIONS IN BULK HANDLING

Robotic manufacturing process ensures consistent high weld quality and assurance of container integrity.

22 5/16" cover with EPDM Gasket and 2" Rieke Fusible Vent/or 3" fusible vent, so cover can remain sealed during filling. 2" bung fitting optional.



2" flush mounted bung fitting.

Lifting Lugs enable container to be lifted overhead via hoist or crane apparatus.



10 Gauge material construction on tank heads and shell.

Available in 304, 316 stainless or painted carbon steel for optimum durability and corrosion resistance.

Temperature control devices can be integrated within an IBC for heating and cooling requirements.

Unique Stamped Bottom provides "no heel" bottom for total drainage.

DOT UN31A permits shipment of flammable and combustible liquids as authorized by Title 49 CFR.

3 Way Fork Entry for both pallet jack and forklift access.

Multiple valve arrangements are available to meet different function and connection requirements.



2" Ball Valve Outlet Assembly



SPECIFICATIONS

Supertainer Standard 42" x 48" Base Tanks			
Tank Size	Top Head Dimension	Overall Height	Approx. Tare Weight
120 Gallon	21.25"	24.6"	302 lbs.
126 Gallon	23.25"	26.6"	315 lbs.
165 Gallon	26.25"	29.6"	326 lbs.
180 Gallon	29.25"	32.6"	340 lbs.
245 Gallon	35.25"	38.6"	389 lbs.
300 Gallon	42.25"	44.6"	424 lbs.
350 Gallon	47.25"	50.6"	469 lbs.
446 Gallon	59.25"	62.6"	542 lbs.
550 Gallon	71.25"	74.6"	612 lbs.
Supertainer 42" x 48" Base, Center Drain Tanks			
350 Gallon	49.50"	52.9"	601 lbs.
550 Gallon	73.50"	76.9"	757 lbs.
550 Gallon TRU-Center	76.50"	79.9"	768 lbs.
Supertainer 54" x 54" Center Drain			
793 Gallon TRU-Center	76.5"	79.9"	1010 lbs.

Supertainer Standard 42" x 42" Base			
Tank Size	Top Head Dimension	Overall Height	Approx. Tare Weight
140 Gallon	26.25"	29.6"	297 lbs.
160 Gallon	29.25"	32.6"	310 lbs.
220 Gallon	35.25"	38.6"	356 lbs.
250 Gallon	41.25"	44.6"	388 lbs.
300 Gallon	47.25"	50.6"	430 lbs.
390 Gallon	59.25"	62.6"	498 lbs.
446 Gallon	71.25"	74.6"	562 lbs.

Additional Options: Sanitary Designs; Center Drain with fork channels; Custom Designs.

Note:

All Center Drain tanks come with 2-way fork channels as standard, but can be removed if needed.

All approximate weights provided are based on stainless steel materials.

Other tank sizes and custom base sizes are available.

OPTIONS & ACCESSORIES

SOLUTIONS IN BULK HANDLING • SOLUTIONS IN BULK HANDLING • SOLUTIONS IN BULK HANDLING • SOLUTIONS IN BULK HANDLING • SOLUTIONS IN BULK HANDLING • SOLUTIONS IN BULK HANDLING • SOLUTIONS IN BULK HANDLING

A wide variety of options and accessories enables you to customize your Supertainer to your application and your budget.



Standard 2" Ball Valve.
Other optional sizes available.



Valve Options
Sanitary, Ball Butterfly



Quick Connect Adapters



Pressure/Vacuum Vents



Drum Lid Clamp Rings
Bolted & Lever-Lock Styles



3" Fusible Vent



2" Rieke Fusible Vent



Crossbar Bung Fittings



Lid Gaskets



Drum Lids in 304 & 316 Stainless Steel & Carbon Steel



2" 15° Offset Male Quick Connect Adapter



3" GITS 5 in 1 Fusible P/V Vent




Insulation Blanket with optional heating elements for all Supertainer sizes.



Replacement Decals



IBC Stands



Cooling/Heating Jacket Panels



Heating Coils: Base Coil; Cork Screw Coil w/protective collar



At-A-Glance Gauge: designed for long-life and easy readability. "At-A-Glance" liquid level indicator.



All Snyder IBCs are available with stacked discharge feed systems that allow the top tank to drain into the bottom tank.



Supertainer is available in carbon steel.

SOLUTIONS IN BULK HANDLING

SOLUTIONS IN BULK HANDLING • SOLUTIONS IN BULK HANDLING • SOLUTIONS IN BULK HANDLING • SOLUTIONS IN BULK HANDLING • SOLUTIONS IN BULK • SOLUTIONS IN BULK HANDLING • SOLUTIONS IN BULK HANDLING



Plastic IBCs

Snyder's unique all polyethylene IBC designs are lightweight, durable and corrosion resistance. Available in a wide variety of shapes and sizes up to 550 gallons, these IBCs are ideal for both hazardous and non-hazardous liquid applications. Rotationally molded-in wall thicknesses up to one half inch, Snyder's plastic IBCs provide some of the industry's highest useful-life-to-cost ratios.



Composite IBCs

Some applications require the combined use of both steel and plastic in an IBC design to meet specific requirements. Snyder offers the industry's broadest range of composite IBCs in sizes up to 550 gallons, where a polyethylene bottle is enclosed in a heavy duty steel cage. Certain plant specifications or warehouse space considerations may require the use of a composite IBC, and Snyder has the perfect solution in these cases.



Viscous Liquid IBCs

Some liquids don't flow freely through a standard IBC bottom discharge design, and require help to drain material efficiently and completely. Snyder has a wide array of IBC design types to promote better drain flow of materials with varying levels of viscosity. Be it a cone bottom or follower plate design, Snyder's viscous liquid IBCs can solve your company's challenges in handling liquid materials with higher viscosities.



Custom Container Designs

In addition to Snyder's extensive standard product offering, some of our greatest success stories stem from custom container designs to meet specific customer requirements. Snyder's engineering team is a recognized leader in design innovation, and is driven to work with customers to develop the best performing container at the lowest possible cost.



Phone: 1-888-IBC-TOTE (888-422-8683) • sales@snydernet.com • www.snyderibcs.com
Snyder Industries, Inc. - Corporate Offices • P.O. Box 4583 • Lincoln, NE • 68504
Other manufacturing Locations: Chowchilla, CA • Mancelona, MI • Marked Tree, AR • Philippi, WV